

# Product Manual

Accent 100 Fixed Type 3



# Accent 100 Fixed Type 3





Recessed ceiling luminaire with rotationally symmetrical flood or wide flood optics, high colour reproduction, fixed orientation, adjustable depth mechanism for optical assembly. Combine with optical lens and anti-glare accessories for oval, wide spread, or diffuse beam control. High pressure die-cast powdercoated facade with snoot detail. Includes direct fast connector to remote driver. Active power factor correction, current regulation, voltage spike protection.

## System

<b>Power</b>	8W / 7W / 14W
<b>Current</b>	180mA / 350mA
<b>Colour Temperature</b>	2700°K / 3000°K / 4000°K / 2700-1800°K Dim to Warm
<b>Lumen Maintenance</b>	L90 B10 50 000hr
<b>CRI</b>	Ra97
<b>Tm30</b>	R95 F103
<b>Chromacity</b>	<2 SCDM
<b>Articulation</b>	355° Rotation / 0° Tilt
<b>Cut-Out</b>	92mm Round x 95-115mm (7W/8W) / 135-155mm (14W) Depth
<b>Ingress Protection</b>	IP20

		<b>FL - 25°</b>	<b>MFL - 40°</b>	<b>WFL - 60°</b>
<b>8W</b>	<b>2700°K</b>	576lm	626lm	624lm
	<b>3000°K</b>	642lm	680lm	672lm
	<b>4000°K</b>	610lm	615lm	650lm
<b>7W</b>	<b>2700-1800°K</b>	454lm	493lm	492lm
<b>14W</b>	<b>2700°K</b>	874lm	863lm	882lm
	<b>3000°K</b>	952lm	931lm	965lm
	<b>4000°K</b>	1044lm	1020lm	1049lm







Accent

Fixed Type 3



Page — 04

# Model References

	FL - 25°	MFL - 40°	WFL - 60°			
<b>8W 2700°K</b>	100 10 000300.011	100 10 000301.011	100 10 000302.011	○	White	Fixed Output
	100 10 000300.021	100 10 000301.021	100 10 000302.021	●	Black	Fixed Output
	100 10 000300.012	100 10 000301.012	100 10 000302.012	○	White	Phase DIM
	100 10 000300.022	100 10 000301.022	100 10 000302.022	●	Black	Phase DIM
	100 10 000300.013	100 10 000301.013	100 10 000302.013	○	White	DALI
	100 10 000300.023	100 10 000301.023	100 10 000302.023	●	Black	DALI
<b>8W 3000°K</b>	100 10 000303.011	100 10 000304.011	100 10 000305.011	○	White	Fixed Output
	100 10 000303.021	100 10 000304.021	100 10 000305.021	●	Black	Fixed Output
	100 10 000303.012	100 10 000304.012	100 10 000305.012	○	White	Phase DIM
	100 10 000303.022	100 10 000304.022	100 10 000305.022	●	Black	Phase DIM
	100 10 000303.013	100 10 000304.013	100 10 000305.013	○	White	DALI
	100 10 000303.023	100 10 000304.023	100 10 000305.023	●	Black	DALI
<b>8W 4000°K</b>	100 10 000306.011	100 10 000307.011	100 10 000308.011	○	White	Fixed Output
	100 10 000306.021	100 10 000307.021	100 10 000308.021	●	Black	Fixed Output
	100 10 000306.012	100 10 000307.012	100 10 000308.012	○	White	Phase DIM
	100 10 000306.022	100 10 000307.022	100 10 000308.022	●	Black	Phase DIM
	100 10 000306.013	100 10 000307.013	100 10 000308.013	○	White	DALI
	100 10 000306.023	100 10 000307.023	100 10 000308.023	●	Black	DALI
<b>7W 2700-1800°K</b>	100 10 000309.011	100 10 000310.011	100 10 000311.011	○	White	Fixed Output
	100 10 000309.021	100 10 000310.021	100 10 000311.021	●	Black	Fixed Output
	100 10 000309.012	100 10 000310.012	100 10 000311.012	○	White	Phase DIM
	100 10 000309.022	100 10 000310.022	100 10 000311.022	●	Black	Phase DIM
	100 10 000309.013	100 10 000310.013	100 10 000311.013	○	White	DALI
	100 10 000309.023	100 10 000310.023	100 10 000311.023	●	Black	DALI
<b>14W 2700°K</b>	100 10 000312.011	100 10 000313.011	100 10 000314.011	○	White	Fixed Output
	100 10 000312.021	100 10 000313.021	100 10 000314.021	●	Black	Fixed Output
	100 10 000312.012	100 10 000313.012	100 10 000314.012	○	White	Phase DIM
	100 10 000312.022	100 10 000313.022	100 10 000314.022	●	Black	Phase DIM
	100 10 000312.013	100 10 000313.013	100 10 000314.013	○	White	DALI
	100 10 000312.023	100 10 000313.023	100 10 000314.023	●	Black	DALI
<b>14W 3000°K</b>	100 10 000315.011	100 10 000316.011	100 10 000317.011	○	White	Fixed Output
	100 10 000315.021	100 10 000316.021	100 10 000317.021	●	Black	Fixed Output
	100 10 000315.012	100 10 000316.012	100 10 000317.012	○	White	Phase DIM
	100 10 000315.022	100 10 000316.022	100 10 000317.022	●	Black	Phase DIM
	100 10 000315.013	100 10 000316.013	100 10 000317.013	○	White	DALI
	100 10 000315.023	100 10 000316.023	100 10 000317.023	●	Black	DALI
<b>14W 4000°K</b>	100 10 000318.011	100 10 000319.011	100 10 000320.011	○	White	Fixed Output
	100 10 000318.021	100 10 000319.021	100 10 000320.021	●	Black	Fixed Output
	100 10 000318.012	100 10 000319.012	100 10 000320.012	○	White	Phase DIM
	100 10 000318.022	100 10 000319.022	100 10 000320.022	●	Black	Phase DIM
	100 10 000318.013	100 10 000319.013	100 10 000320.013	○	White	DALI
	100 10 000318.023	100 10 000319.023	100 10 000320.023	●	Black	DALI
<b>Accessories</b>	980 00 004301.010	Hex Louvre 043				
	980 00 004302.000	Spreader Lens 043				
	980 00 004303.000	Linear Spreader Lens 043				
	980 00 004304.000	Diffuser Lens 043				

iilus.com