

# Product Manual

Accent 100 Trimless Concrete Fixed Type 1



# Accent 100 Trimless Concrete Fixed Type 1




Recessed ceiling luminaire for use in concrete slab with rotationally symmetrical flood or wide flood optics, high colour reproduction, fixed orientation, adjustable depth mechanism for optical assembly. Combine with optical lens and anti-glare accessories for oval, wide spread, or diffuse beam control. High pressure die-cast powdercoated facade with inset detail. Includes direct fast connector to remote driver. Active power factor correction, current regulation, voltage spike protection.

## System

<b>Power</b>	8W / 7W / 14W
<b>Current</b>	180mA / 350mA
<b>Colour Temperature</b>	2700°K / 3000°K / 4000°K / 2700-1800°K Dim to Warm
<b>Lumen Maintenance</b>	L90 B10 50 000hr
<b>CRI</b>	Ra97
<b>Tm30</b>	R95 F103
<b>Chromacity</b>	<2 SCDM
<b>Articulation</b>	355° Rotation / 0° Tilt
<b>Cavity</b>	182mm Round x 125-190mm Depth
<b>Ingress Protection</b>	IP20

		<b>FL - 25°</b>	<b>MFL - 40°</b>	<b>WFL - 60°</b>
<b>8W</b>	<b>2700°K</b>	576lm	626lm	624lm
	<b>3000°K</b>	642lm	680lm	672lm
	<b>4000°K</b>	610lm	615lm	650lm
<b>7W</b>	<b>2700-1800°K</b>	454lm	493lm	492lm
<b>14W</b>	<b>2700°K</b>	874lm	863lm	882lm
	<b>3000°K</b>	952lm	931lm	965lm
	<b>4000°K</b>	1044lm	1020lm	1049lm







# Accent 100 Trimless Concrete Fixed Type 1

	FL - 25°	MFL - 40°	WFL - 60°			
<b>8W 2700°K</b>	100 10 012100.011	100 10 012101.011	100 10 012102.011	○	White	Fixed Output
	100 10 012100.021	100 10 012101.021	100 10 012102.021	●	Black	Fixed Output
	100 10 012100.012	100 10 012101.012	100 10 012102.012	○	White	Phase DIM
	100 10 012100.022	100 10 012101.022	100 10 012102.022	●	Black	Phase DIM
	100 10 012100.013	100 10 012101.013	100 10 012102.013	○	White	DALI
	100 10 012100.023	100 10 012101.023	100 10 012102.023	●	Black	DALI
<b>8W 3000°K</b>	100 10 012103.011	100 10 012104.011	100 10 012105.011	○	White	Fixed Output
	100 10 012103.021	100 10 012104.021	100 10 012105.021	●	Black	Fixed Output
	100 10 012103.012	100 10 012104.012	100 10 012105.012	○	White	Phase DIM
	100 10 012103.022	100 10 012104.022	100 10 012105.022	●	Black	Phase DIM
	100 10 012103.013	100 10 012104.013	100 10 012105.013	○	White	DALI
	100 10 012103.023	100 10 012104.023	100 10 012105.023	●	Black	DALI
<b>8W 4000°K</b>	100 10 012106.011	100 10 012107.011	100 10 012108.011	○	White	Fixed Output
	100 10 012106.021	100 10 012107.021	100 10 012108.021	●	Black	Fixed Output
	100 10 012106.012	100 10 012107.012	100 10 012108.012	○	White	Phase DIM
	100 10 012106.022	100 10 012107.022	100 10 012108.022	●	Black	Phase DIM
	100 10 012106.013	100 10 012107.013	100 10 012108.013	○	White	DALI
	100 10 012106.023	100 10 012107.023	100 10 012108.023	●	Black	DALI
<b>7W 2700-1800°K</b>	100 10 012109.011	100 10 012110.011	100 10 012111.011	○	White	Fixed Output
	100 10 012109.021	100 10 012110.021	100 10 012111.021	●	Black	Fixed Output
	100 10 012109.012	100 10 012110.012	100 10 012111.012	○	White	Phase DIM
	100 10 012109.022	100 10 012110.022	100 10 012111.022	●	Black	Phase DIM
	100 10 012109.013	100 10 012110.013	100 10 012111.013	○	White	DALI
	100 10 012109.023	100 10 012110.023	100 10 012111.023	●	Black	DALI
<b>14W 2700°K</b>	100 10 012112.011	100 10 012113.011	100 10 012114.011	○	White	Fixed Output
	100 10 012112.021	100 10 012113.021	100 10 012114.021	●	Black	Fixed Output
	100 10 012112.012	100 10 012113.012	100 10 012114.012	○	White	Phase DIM
	100 10 012112.022	100 10 012113.022	100 10 012114.022	●	Black	Phase DIM
	100 10 012112.013	100 10 012113.013	100 10 012114.013	○	White	DALI
	100 10 012112.023	100 10 012113.023	100 10 012114.023	●	Black	DALI
<b>14W 3000°K</b>	100 10 012115.011	100 10 012116.011	100 10 012117.011	○	White	Fixed Output
	100 10 012115.021	100 10 012116.021	100 10 012117.021	●	Black	Fixed Output
	100 10 012115.012	100 10 012116.012	100 10 012117.012	○	White	Phase DIM
	100 10 012115.022	100 10 012116.022	100 10 012117.022	●	Black	Phase DIM
	100 10 012115.013	100 10 012116.013	100 10 012117.013	○	White	DALI
	100 10 012115.023	100 10 012116.023	100 10 012117.023	●	Black	DALI
<b>14W 4000°K</b>	100 10 012118.011	100 10 012119.011	100 10 012120.011	○	White	Fixed Output
	100 10 012118.021	100 10 012119.021	100 10 012120.021	●	Black	Fixed Output
	100 10 012118.012	100 10 012119.012	100 10 012120.012	○	White	Phase DIM
	100 10 012118.022	100 10 012119.022	100 10 012120.022	●	Black	Phase DIM
	100 10 012118.013	100 10 012119.013	100 10 012120.013	○	White	DALI
	100 10 012118.023	100 10 012119.023	100 10 012120.023	●	Black	DALI
<b>Accessories</b>	980 00 004301.010	Hex Louvre 043				
	980 00 004302.000	Spreader Lens 043				
	980 00 004303.000	Linear Spreader Lens 043				
	980 00 004304.000	Diffuser Lens 043				

iilus.com