

# Product Manual

Accent 100 Trimless Concrete Fixed Type 2



# Accent 100 Trimless Concrete Fixed Type 2




Recessed ceiling luminaire for use in concrete slab with rotationally symmetrical flood or wide flood optics, high colour reproduction, fixed orientation, adjustable depth mechanism for optical assembly. Combine with optical lens and anti-glare accessories for oval, wide spread, or diffuse beam control. High pressure die-cast powdercoated facade with rounded detail. Includes direct fast connector to remote driver. Active power factor correction, current regulation, voltage spike protection.

## System

<b>Power</b>	8W / 7W / 14W
<b>Current</b>	180mA / 350mA
<b>Colour Temperature</b>	2700°K / 3000°K / 4000°K / 2700-1800°K Dim to Warm
<b>Lumen Maintenance</b>	L90 B10 50 000hr
<b>CRI</b>	Ra97
<b>Tm30</b>	R95 F103
<b>Chromacity</b>	<2 SCDM
<b>Articulation</b>	355° Rotation / 0° Tilt
<b>Cavity</b>	182mm Round x 125-190mm Depth
<b>Ingress Protection</b>	IP20

		<b>FL - 25°</b>	<b>MFL - 40°</b>	<b>WFL - 60°</b>
<b>8W</b>	<b>2700°K</b>	576lm	626lm	624lm
	<b>3000°K</b>	642lm	680lm	672lm
	<b>4000°K</b>	610lm	615lm	650lm
<b>7W</b>	<b>2700-1800°K</b>	454lm	493lm	492lm
<b>14W</b>	<b>2700°K</b>	874lm	863lm	882lm
	<b>3000°K</b>	952lm	931lm	965lm
	<b>4000°K</b>	1044lm	1020lm	1049lm







# Accent 100 Trimless Concrete Fixed Type 2

	FL - 25°	MFL - 40°	WFL - 60°			
<b>8W 2700°K</b>	100 10 012200.011	100 10 012201.011	100 10 012202.011	○	White	Fixed Output
	100 10 012200.021	100 10 012201.021	100 10 012202.021	●	Black	Fixed Output
	100 10 012200.012	100 10 012201.012	100 10 012202.012	○	White	Phase DIM
	100 10 012200.022	100 10 012201.022	100 10 012202.022	●	Black	Phase DIM
	100 10 012200.013	100 10 012201.013	100 10 012202.013	○	White	DALI
	100 10 012200.023	100 10 012201.023	100 10 012202.023	●	Black	DALI
<b>8W 3000°K</b>	100 10 012203.011	100 10 012204.011	100 10 012205.011	○	White	Fixed Output
	100 10 012203.021	100 10 012204.021	100 10 012205.021	●	Black	Fixed Output
	100 10 012203.012	100 10 012204.012	100 10 012205.012	○	White	Phase DIM
	100 10 012203.022	100 10 012204.022	100 10 012205.022	●	Black	Phase DIM
	100 10 012203.013	100 10 012204.013	100 10 012205.013	○	White	DALI
	100 10 012203.023	100 10 012204.023	100 10 012205.023	●	Black	DALI
<b>8W 4000°K</b>	100 10 012206.011	100 10 012207.011	100 10 012208.011	○	White	Fixed Output
	100 10 012206.021	100 10 012207.021	100 10 012208.021	●	Black	Fixed Output
	100 10 012206.012	100 10 012207.012	100 10 012208.012	○	White	Phase DIM
	100 10 012206.022	100 10 012207.022	100 10 012208.022	●	Black	Phase DIM
	100 10 012206.013	100 10 012207.013	100 10 012208.013	○	White	DALI
	100 10 012206.023	100 10 012207.023	100 10 012208.023	●	Black	DALI
<b>7W 2700-1800°K</b>	100 10 012209.011	100 10 012210.011	100 10 012211.011	○	White	Fixed Output
	100 10 012209.021	100 10 012210.021	100 10 012211.021	●	Black	Fixed Output
	100 10 012209.012	100 10 012210.012	100 10 012211.012	○	White	Phase DIM
	100 10 012209.022	100 10 012210.022	100 10 012211.022	●	Black	Phase DIM
	100 10 012209.013	100 10 012210.013	100 10 012211.013	○	White	DALI
	100 10 012209.023	100 10 012210.023	100 10 012211.023	●	Black	DALI
<b>14W 2700°K</b>	100 10 012212.011	100 10 012213.011	100 10 012214.011	○	White	Fixed Output
	100 10 012212.021	100 10 012213.021	100 10 012214.021	●	Black	Fixed Output
	100 10 012212.012	100 10 012213.012	100 10 012214.012	○	White	Phase DIM
	100 10 012212.022	100 10 012213.022	100 10 012214.022	●	Black	Phase DIM
	100 10 012212.013	100 10 012213.013	100 10 012214.013	○	White	DALI
	100 10 012212.023	100 10 012213.023	100 10 012202.023	●	Black	DALI
<b>14W 3000°K</b>	100 10 012215.011	100 10 012216.011	100 10 012217.011	○	White	Fixed Output
	100 10 012215.021	100 10 012216.021	100 10 012217.021	●	Black	Fixed Output
	100 10 012215.012	100 10 012216.012	100 10 012217.012	○	White	Phase DIM
	100 10 012215.022	100 10 012216.022	100 10 012217.022	●	Black	Phase DIM
	100 10 012215.013	100 10 012216.013	100 10 012217.013	○	White	DALI
	100 10 012215.023	100 10 012216.023	100 10 012217.023	●	Black	DALI
<b>14W 4000°K</b>	100 10 012218.011	100 10 012219.011	100 10 012220.011	○	White	Fixed Output
	100 10 012218.021	100 10 012219.021	100 10 012220.021	●	Black	Fixed Output
	100 10 012218.012	100 10 012219.012	100 10 012220.012	○	White	Phase DIM
	100 10 012218.022	100 10 012219.022	100 10 012220.022	●	Black	Phase DIM
	100 10 012218.013	100 10 012219.013	100 10 012220.013	○	White	DALI
	100 10 012218.023	100 10 012219.023	100 10 012220.023	●	Black	DALI
<b>Accessories</b>	980 00 004301.010	Hex Louvre 043				
	980 00 004302.000	Spreader Lens 043				
	980 00 004303.000	Linear Spreader Lens 043				
	980 00 004304.000	Diffuser Lens 043				

iilus.com