

# Product Manual

Accent 100 IP Trimless Concrete Fixed Type 3



# Accent 100 IP Trimless Concrete Fixed Type 3




Recessed ceiling luminaire for use in concrete slab with rotationally symmetrical flood or wide flood optics, high colour reproduction, fixed orientation, adjustable depth mechanism for optical assembly. Combine with optical lens and anti-glare accessories for oval, wide spread, or diffuse beam control. High pressure die-cast powdercoated facade from marine-grade base material and nano-ceramic pre-treatment with snoot detail. Includes direct fast connector to remote driver. Active power factor correction, current regulation, voltage spike protection.

## System

<b>Power</b>	8W / 7W / 14W
<b>Current</b>	180mA / 350mA
<b>Colour Temperature</b>	2700°K / 3000°K / 4000°K / 2700-1800°K Dim to Warm
<b>Lumen Maintenance</b>	L90 B10 50 000hr
<b>CRI</b>	Ra97
<b>Tm30</b>	R95 F103
<b>Chromacity</b>	<2 SCDM
<b>Articulation</b>	355° Rotation / 0° Tilt
<b>Cavity</b>	182mm Round x 125-190mm Depth
<b>Ingress Protection</b>	IP44

		<b>FL - 25°</b>	<b>MFL - 40°</b>	<b>WFL - 60°</b>
<b>8W</b>	<b>2700°K</b>	576lm	626lm	624lm
	<b>3000°K</b>	642lm	680lm	672lm
	<b>4000°K</b>	610lm	615lm	650lm
<b>7W</b>	<b>2700-1800°K</b>	454lm	493lm	492lm
<b>14W</b>	<b>2700°K</b>	874lm	863lm	882lm
	<b>3000°K</b>	952lm	931lm	965lm
	<b>4000°K</b>	1044lm	1020lm	1049lm







# Accent 100 IP Trimless Concrete Fixed Type 3

	FL - 25°	MFL - 40°	WFL - 60°			
<b>8W 2700°K</b>	100 10 015300.011	100 10 015301.011	100 10 015302.011	○	White	Fixed Output
	100 10 015300.021	100 10 015301.021	100 10 015302.021	●	Black	Fixed Output
	100 10 015300.012	100 10 015301.012	100 10 015302.012	○	White	Phase DIM
	100 10 015300.022	100 10 015301.022	100 10 015302.022	●	Black	Phase DIM
	100 10 015300.013	100 10 015301.013	100 10 015302.013	○	White	DALI
	100 10 015300.023	100 10 015301.023	100 10 015302.023	●	Black	DALI
<b>8W 3000°K</b>	100 10 015303.011	100 10 015304.011	100 10 015305.011	○	White	Fixed Output
	100 10 015303.021	100 10 015304.021	100 10 015305.021	●	Black	Fixed Output
	100 10 015303.012	100 10 015304.012	100 10 015305.012	○	White	Phase DIM
	100 10 015303.022	100 10 015304.022	100 10 015305.022	●	Black	Phase DIM
	100 10 015303.013	100 10 015304.013	100 10 015305.013	○	White	DALI
	100 10 015303.023	100 10 015304.023	100 10 015305.023	●	Black	DALI
<b>8W 4000°K</b>	100 10 015306.011	100 10 015307.011	100 10 015308.011	○	White	Fixed Output
	100 10 015306.021	100 10 015307.021	100 10 015308.021	●	Black	Fixed Output
	100 10 015306.012	100 10 015307.012	100 10 015308.012	○	White	Phase DIM
	100 10 015306.022	100 10 015307.022	100 10 015308.022	●	Black	Phase DIM
	100 10 015306.013	100 10 015307.013	100 10 015308.013	○	White	DALI
	100 10 015306.023	100 10 015307.023	100 10 015308.023	●	Black	DALI
<b>7W 2700-1800°K</b>	100 10 015309.011	100 10 015310.011	100 10 015311.011	○	White	Fixed Output
	100 10 015309.021	100 10 015310.021	100 10 015311.021	●	Black	Fixed Output
	100 10 015309.012	100 10 015310.012	100 10 015311.012	○	White	Phase DIM
	100 10 015309.022	100 10 015310.022	100 10 015311.022	●	Black	Phase DIM
	100 10 015309.013	100 10 015310.013	100 10 015311.013	○	White	DALI
	100 10 015309.023	100 10 015310.023	100 10 015311.023	●	Black	DALI
<b>14W 2700°K</b>	100 10 015312.011	100 10 015313.011	100 10 015314.011	○	White	Fixed Output
	100 10 015312.021	100 10 015313.021	100 10 015314.021	●	Black	Fixed Output
	100 10 015312.012	100 10 015313.012	100 10 015314.012	○	White	Phase DIM
	100 10 015312.022	100 10 015313.022	100 10 015314.022	●	Black	Phase DIM
	100 10 015312.013	100 10 015313.013	100 10 015314.013	○	White	DALI
	100 10 015312.023	100 10 015313.023	100 10 015314.023	●	Black	DALI
<b>14W 3000°K</b>	100 10 015315.011	100 10 015316.011	100 10 015317.011	○	White	Fixed Output
	100 10 015315.021	100 10 015316.021	100 10 015317.021	●	Black	Fixed Output
	100 10 015315.012	100 10 015316.012	100 10 015317.012	○	White	Phase DIM
	100 10 015315.022	100 10 015316.022	100 10 015317.022	●	Black	Phase DIM
	100 10 015315.013	100 10 015316.013	100 10 015317.013	○	White	DALI
	100 10 015315.023	100 10 015316.023	100 10 015317.023	●	Black	DALI
<b>14W 4000°K</b>	100 10 015318.011	100 10 015319.011	100 10 015320.011	○	White	Fixed Output
	100 10 015318.021	100 10 015319.021	100 10 015320.021	●	Black	Fixed Output
	100 10 015318.012	100 10 015319.012	100 10 015320.012	○	White	Phase DIM
	100 10 015318.022	100 10 015319.022	100 10 015320.022	●	Black	Phase DIM
	100 10 015318.013	100 10 015319.013	100 10 015320.013	○	White	DALI
	100 10 015318.023	100 10 015319.023	100 10 015320.023	●	Black	DALI
<b>Accessories</b>	980 00 004301.010	Hex Louvre 043				
	980 00 004302.000	Spreader Lens 043				
	980 00 004303.000	Linear Spreader Lens 043				
	980 00 004304.000	Diffuser Lens 043				

iilus.com