

# Product Manual

Mono 060 Recessed Downlighter Type 3



# Mono 060 Recessed Type 3




Recessed ceiling luminaire with rotationally symmetrical medium, flood or wide flood optics, high colour reproduction, fixed orientation. High pressure die-cast powdercoated facade with snoot and shallow recess depth. Includes direct fast connector to remote driver. Active power factor correction, current regulation, voltage spike protection.

## System

<b>Power</b>	8W
<b>Current</b>	180mA
<b>Colour Temperature</b>	2700°K / 3000°K / 4000°K / 2700-1800°K
<b>Lumen Maintenance</b>	L90 B10 50 000hr
<b>CRI</b>	Ra97
<b>Tm30</b>	R95 F103
<b>Chromacity</b>	<3 SCDM
<b>Articulation</b>	Fixed
<b>Cut-Out</b>	54mm Round x 75mm Depth
<b>Ingress Protection</b>	IP44

	<b>FL - 25°</b>	<b>MFL - 40°</b>	<b>WFL - 60°</b>
<b>2700°K</b>	576lm	626lm	624lm
<b>3000°K</b>	642lm	680lm	672lm
<b>4000°K</b>	610lm	615lm	650lm







Mono

Type 3



Page — 04

# Model References

	FL - 25°	MFL - 40°	WFL - 60°		
<b>2700°K</b>	101 06 000300.011	101 06 000301.011	101 06 000302.011	White	Fixed Output
	101 06 000300.021	101 06 000301.021	101 06 000302.021	Black	Fixed Output
	101 06 000300.012	101 06 000301.012	101 06 000302.012	White	Phase DIM
	101 06 000300.022	101 06 000301.022	101 06 000302.022	Black	Phase DIM
	101 06 000300.013	101 06 000301.013	101 06 000302.013	White	DALI
	101 06 000300.023	101 06 000301.023	101 06 000302.023	Black	DALI
<b>3000°K</b>	101 06 000303.011	101 06 000304.011	101 06 000305.011	White	Fixed Output
	101 06 000303.021	101 06 000304.021	101 06 000305.021	Black	Fixed Output
	101 06 000303.012	101 06 000304.012	101 06 000305.012	White	Phase DIM
	101 06 000303.022	101 06 000304.022	101 06 000305.022	Black	Phase DIM
	101 06 000303.013	101 06 000304.013	101 06 000305.013	White	DALI
	101 06 000303.023	101 06 000304.023	101 06 000305.023	Black	DALI
<b>4000°K</b>	101 06 000306.011	101 06 000307.011	101 06 000308.011	White	Fixed Output
	101 06 000306.021	101 06 000307.021	101 06 000308.021	Black	Fixed Output
	101 06 000306.012	101 06 000307.012	101 06 000308.012	White	Phase DIM
	101 06 000306.022	101 06 000307.022	101 06 000308.022	Black	Phase DIM
	101 06 000306.013	101 06 000307.013	101 06 000308.013	White	DALI
	101 06 000306.023	101 06 000307.023	101 06 000308.023	Black	DALI
<b>2700-1800°K</b>	101 06 000309.011	101 06 000310.011	101 06 000311.011	White	Fixed Output
	101 06 000309.021	101 06 000310.021	101 06 000311.021	Black	Fixed Output
	101 06 000309.012	101 06 000310.012	101 06 000311.012	White	Phase DIM
	101 06 000309.022	101 06 000310.022	101 06 000311.022	Black	Phase DIM
	101 06 000309.013	101 06 000310.013	101 06 000311.013	White	DALI
	101 06 000309.023	101 06 000310.023	101 06 000311.023	Black	DALI

iilus.com