

# Product Manual

Mono 060 Surface Downlighter Type 1



# Mono 060 Surface Type 1




Surface mounted ceiling luminaire with rotationally symmetrical medium, flood or wide flood optics, high colour reproduction, fixed orientation. Extruded aluminium housing with high pressure die-cast powdercoated facade and inset detail. Integrated driver. Active power factor correction, current regulation, voltage spike protection.

## System

<b>Power</b>	8W
<b>Current</b>	180mA
<b>Colour Temperature</b>	2700°K / 3000°K / 4000°K / 2700-1800°K
<b>Lumen Maintenance</b>	L90 B10 50 000hr
<b>CRI</b>	Ra97
<b>Tm30</b>	R95 F103
<b>Chromacity</b>	<3 SCDM
<b>Articulation</b>	Fixed
<b>Ingress Protection</b>	IP20

	<b>FL - 25°</b>	<b>MFL - 40°</b>	<b>WFL - 60°</b>
<b>2700°K</b>	576lm	626lm	624lm
<b>3000°K</b>	642lm	680lm	672lm
<b>4000°K</b>	610lm	615lm	650lm







# Model References

	FL - 25°	MFL - 40°	WFL - 60°		
<b>2700°K</b>	101 06 100100.012	101 06 100101.012	101 06 100102.012	White	Phase DIM
	101 06 100100.022	101 06 100101.022	101 06 100102.022	Black	Phase DIM
<b>3000°K</b>	101 06 100103.012	101 06 100104.012	101 06 100105.012	White	Phase DIM
	101 06 100103.022	101 06 100104.022	101 06 100105.022	Black	Phase DIM
<b>4000°K</b>	101 06 100106.012	101 06 100107.012	101 06 100108.012	White	Phase DIM
	101 06 100106.022	101 06 100107.022	101 06 100108.022	Black	Phase DIM
<b>2700°K</b>	101 06 100100.012	101 06 100101.012	101 06 100102.012	White	Control Excluded
	101 06 100100.022	101 06 100101.022	101 06 100102.022	Black	Control Excluded
<b>3000°K</b>	101 06 100103.012	101 06 100104.012	101 06 100105.012	White	Control Excluded
	101 06 100103.022	101 06 100104.022	101 06 100105.022	Black	Control Excluded
<b>4000°K</b>	101 06 100106.012	101 06 100107.012	101 06 100108.012	White	Control Excluded
	101 06 100106.022	101 06 100107.022	101 06 100108.022	Black	Control Excluded
<b>2700-1800°K</b>	101 06 100109.010	101 06 100110.010	101 06 100111.010	White	Control Excluded
	101 06 100109.020	101 06 100110.020	101 06 100111.020	Black	Control Excluded
<b>Remote Drivers</b>	981 00 000818.022	CC LED Driver 8W 180mA LE-TE P1S1			Phase DIM
	981 00 202018.023	CC-CV LED Driver 9W 180mA DALI P1S1			DALI

iilus.com