

Product Manual

Mono 060 Surface Downlighter Type 2



Mono 060 Surface Type 2




Surface mounted ceiling luminaire with rotationally symmetrical medium, flood or wide flood optics, high colour reproduction, fixed orientation. Extruded aluminium housing with high pressure die-cast powdercoated facade and anti-glare baffle. Integrated driver. Active power factor correction, current regulation, voltage spike protection.


System

Power	8W
Current	180mA
Colour Temperature	2700°K / 3000°K / 4000°K / 2700-1800°K
Lumen Maintenance	L90 B10 50 000hr
CRI	Ra97
Tm30	R95 F103
Chromacity	<3 SCDM
Articulation	Fixed
Ingress Protection	IP20

	FL - 25°	MFL - 40°	WFL - 60°
2700°K	576lm	626lm	624lm
3000°K	642lm	680lm	672lm
4000°K	610lm	615lm	650lm







Model References

	FL - 25°	MFL - 40°	WFL - 60°		
2700°K	101 06 100200.012	101 06 100201.012	101 06 100202.012	White	Phase DIM
	101 06 100200.022	101 06 100201.022	101 06 100202.022	Black	Phase DIM
3000°K	101 06 100203.012	101 06 100204.012	101 06 100205.012	White	Phase DIM
	101 06 100203.022	101 06 100204.022	101 06 100205.022	Black	Phase DIM
4000°K	101 06 100206.012	101 06 100207.012	101 06 100208.012	White	Phase DIM
	101 06 100206.022	101 06 100207.022	101 06 100208.022	Black	Phase DIM
2700°K	101 06 100200.012	101 06 100201.012	101 06 100202.012	White	Control Excluded
	101 06 100200.022	101 06 100201.022	101 06 100202.022	Black	Control Excluded
3000°K	101 06 100203.012	101 06 100204.012	101 06 100205.012	White	Control Excluded
	101 06 100203.022	101 06 100204.022	101 06 100205.022	Black	Control Excluded
4000°K	101 06 100206.012	101 06 100207.012	101 06 100208.012	White	Control Excluded
	101 06 100206.022	101 06 100207.022	101 06 100208.022	Black	Control Excluded
2700-1800°K	101 06 100209.010	101 06 100210.010	101 06 100211.010	White	Control Excluded
	101 06 100209.020	101 06 100210.020	101 06 100211.020	Black	Control Excluded
Remote Drivers	981 00 000818.022	CC LED Driver 8W 180mA LE-TE P1S1			Phase DIM
	981 00 202018.023	CC-CV LED Driver 9W 180mA DALI P1S1			DALI

iilus.com