

Product Manual

Mono 060 IP Surface Downlighter Type 2



Mono 060 IP Surface Type 2




Surface mounted ceiling luminaire with rotationally symmetrical medium, flood or wide flood optics, high colour reproduction, fixed orientation. Extruded marine-grade aluminium housing with nano-ceramic pre-treatment, high pressure die-cast powdercoated facade and anti-glare baffle detail. Integrated driver. Active power factor correction, current regulation, voltage spike protection.

System

Power	8W
Current	180mA
Colour Temperature	2700°K / 3000°K / 4000°K / 2700-1800°K
Lumen Maintenance	L90 B10 50 000hr
CRI	Ra97
Tm30	R95 F103
Chromacity	<3 SCDM
Articulation	Fixed
Ingress Protection	IP54

	FL - 25°	MFL - 40°	WFL - 60°
2700°K	576lm	626lm	624lm
3000°K	642lm	680lm	672lm
4000°K	610lm	615lm	650lm







Mono IP

Type 2



Page — 04

Model References

	FL - 25°	MFL - 40°	WFL - 60°		
2700°K	101 06 101200.012	101 06 101201.012	101 06 101202.012	White	Phase DIM
	101 06 101200.022	101 06 101201.022	101 06 101202.022	Black	Phase DIM
3000°K	101 06 101203.012	101 06 101204.012	101 06 101205.012	White	Phase DIM
	101 06 101203.022	101 06 101204.022	101 06 101205.022	Black	Phase DIM
4000°K	101 06 101206.012	101 06 101207.012	101 06 101208.012	White	Phase DIM
	101 06 101206.022	101 06 101207.022	101 06 101208.022	Black	Phase DIM
2700°K	101 06 101200.012	101 06 101201.012	101 06 101202.012	White	Control Excluded
	101 06 101200.022	101 06 101201.022	101 06 101202.022	Black	Control Excluded
3000°K	101 06 101203.012	101 06 101204.012	101 06 101205.012	White	Control Excluded
	101 06 101203.022	101 06 101204.022	101 06 101205.022	Black	Control Excluded
4000°K	101 06 101206.012	101 06 101207.012	101 06 101208.012	White	Control Excluded
	101 06 101206.022	101 06 101207.022	101 06 101208.022	Black	Control Excluded
2700-1800°K	101 06 101209.010	101 06 101210.010	101 06 101211.010	White	Control Excluded
	101 06 101209.020	101 06 101210.020	101 06 101211.020	Black	Control Excluded
Remote Drivers	981 00 000818.022	CC LED Driver 8W 180mA LE-TE P1S1			Phase DIM
	981 00 202018.023	CC-CV LED Driver 9W 180mA DALI P1S1			DALI

iilus.com