

Product Manual


Mono 060 Suspension Type 1



Mono 060 Suspension Type 1



Ceiling suspension luminaire with rotationally symmetrical medium, flood or wide flood optics, high colour reproduction, fixed orientation. Extruded aluminium housing with high pressure die-cast powdercoated facade and inset detail. Integrated driver. Active power factor correction, current regulation, voltage spike protection.



System

Power	8W				
Input	220V-240V — 50/60Hz				
Colour Temperature	2700°K — 3000°K				
Lumen Maintenance	L90 B10 50 000hr				
CRI	Ra98				
Tm30	R95 F103				
Chromacity	<3 SCDM				
Articulation	Fixed				
Ingress Protection	IP20				
	M - 25°	FL - 40°	WFL - 60°		
2700°K	576lm	626lm	624lm		
3000°K	642lm	680lm	672lm		
2700°K	101 06 200100.012	101 06 200101.012	101 06 200102.012	White	Phase DIM
	101 06 200100.022	101 06 200101.022	101 06 200102.022	Black	Phase DIM
3000°K	101 06 200103.012	101 06 200104.012	101 06 200105.012	White	Phase DIM
	101 06 200103.022	101 06 200104.022	101 06 200105.022	Black	Phase DIM







iilus.com