

# Product Manual

Mono 100 Recessed Downlighter Type 3




# Mono 100

## Type 3



Recessed ceiling luminaire with rotationally symmetrical spot, flood or wide flood optics, high colour reproduction, fixed orientation. High pressure die-cast powdercoated facade with snoot detail for prevention of glare. Includes direct fast connector to remote driver. Active power factor correction, current regulation, voltage spike protection. Optional spreader lens, linear spreader lens, diffuser lens, or hex louvre; factory fitted.



### System

<b>Power</b>	14W / 19W / 27W
<b>Input</b>	220V-240V / 50-60Hz
<b>Colour Temperature</b>	2700°K / 3000°K / 4000°K
<b>Lumen Maintenance</b>	L90 B10 50 000hr
<b>CRI</b>	Ra97
<b>Tm30</b>	Rf95 Rg103
<b>Chromacity</b>	<3 SCDM
<b>Articulation</b>	Fixed
<b>Ingress Protection</b>	IP44

14W	SP - 15°	FL - 30°	WFL - 60°
2700°K	956lm	1013lm	981lm
3000°K	953lm	942lm	1037lm
4000°K	1127lm	1095lm	1132lm
19W	SP - 15°	FL - 30°	WFL - 60°
2700°K	1314lm	1300lm	1350lm
3000°K	1320lm	1300lm	1436lm
4000°K	1548lm	1508lm	1568lm
27W	SP - 15°	FL - 30°	WFL - 60°
2700°K	1763lm	1750lm	1765lm
3000°K	1781lm	1770lm	1939lm
4000°K	2091lm	2029lm	2110lm





- Hex Louvre ▲
- Linear Spreader Lens ►
- Spreader Lens ►
- Diffuser Lens ►







- Hex Louvre ▲
- Linear Spreader Lens ▲
- Diffuser Lens ►
- Spreader Lens ►

# Model References

14W	SP - 15°	FL - 30°	WFL - 60°		
<b>2700°K</b>	101 10 000300.011	101 10 000301.011	101 10 000302.011	White	Fixed Output
	101 10 000300.211	101 10 000301.021	101 10 000302.021	Black	Fixed Output
	101 10 000300.012	101 10 000301.012	101 10 000302.012	White	Phase DIM
	101 10 000300.212	101 10 000301.022	101 10 000302.022	Black	Phase DIM
	101 10 000300.013	101 10 000301.013	101 10 000302.013	White	DALI
	101 10 000300.213	101 10 000301.023	101 10 000302.023	Black	DALI
	101 10 000300.015	101 10 000301.015	101 10 000302.015	White	Bluetooth
	101 10 000300.215	101 10 000301.025	101 10 000302.025	Black	Bluetooth
<b>3000°K</b>	101 10 000303.011	101 10 000304.011	101 10 000305.011	White	Fixed Output
	101 10 000303.211	101 10 000304.021	101 10 000305.021	Black	Fixed Output
	101 10 000303.012	101 10 000304.012	101 10 000305.012	White	Phase DIM
	101 10 000303.212	101 10 000304.022	101 10 000305.022	Black	Phase DIM
	101 10 000303.013	101 10 000304.013	101 10 000305.013	White	DALI
	101 10 000303.213	101 10 000304.023	101 10 000305.023	Black	DALI
	101 10 000303.015	101 10 000304.015	101 10 000305.015	White	Bluetooth
	101 10 000303.215	101 10 000304.025	101 10 000305.025	Black	Bluetooth
<b>4000°K</b>	101 10 000306.011	101 10 000307.011	101 10 000308.011	White	Fixed Output
	101 10 000306.211	101 10 000307.021	101 10 000308.021	Black	Fixed Output
	101 10 000306.012	101 10 000307.012	101 10 000308.012	White	Phase DIM
	101 10 000306.212	101 10 000307.022	101 10 000308.022	Black	Phase DIM
	101 10 000306.013	101 10 000307.013	101 10 000308.013	White	DALI
	101 10 000306.213	101 10 000307.023	101 10 000308.023	Black	DALI
	101 10 000306.015	101 10 000307.015	101 10 000308.015	White	Bluetooth
	101 10 000306.215	101 10 000307.025	101 10 000308.025	Black	Bluetooth



19W	SP - 15°	FL - 30°	WFL - 60°		
2700°K	101 10 000309.011	101 10 000310.011	101 10 000311.011	White	Fixed Output
	101 10 000309.211	101 10 000310.021	101 10 000311.021	Black	Fixed Output
	101 10 000309.012	101 10 000310.012	101 10 000311.012	White	Phase DIM
	101 10 000309.212	101 10 000310.022	101 10 000311.022	Black	Phase DIM
	101 10 000309.013	101 10 000310.013	101 10 000311.013	White	DALI
	101 10 000309.213	101 10 000310.023	101 10 000311.023	Black	DALI
	101 10 000309.015	101 10 000310.015	101 10 000311.015	White	Bluetooth
	101 10 000309.215	101 10 000310.025	101 10 000311.025	Black	Bluetooth
3000°K	101 10 000312.011	101 10 000313.011	101 10 000314.011	White	Fixed Output
	101 10 000312.211	101 10 000313.021	101 10 000314.021	Black	Fixed Output
	101 10 000312.012	101 10 000313.012	101 10 000314.012	White	Phase DIM
	101 10 000312.212	101 10 000313.022	101 10 000314.022	Black	Phase DIM
	101 10 000312.013	101 10 000313.013	101 10 000314.013	White	DALI
	101 10 000312.213	101 10 000313.023	101 10 000314.023	Black	DALI
	101 10 000312.015	101 10 000313.015	101 10 000314.015	White	Bluetooth
	101 10 000312.215	101 10 000313.025	101 10 000314.025	Black	Bluetooth
4000°K	101 10 000315.011	101 10 000316.011	101 10 000317.011	White	Fixed Output
	101 10 000315.211	101 10 000316.021	101 10 000317.021	Black	Fixed Output
	101 10 000315.012	101 10 000316.012	101 10 000317.012	White	Phase DIM
	101 10 000315.212	101 10 000316.022	101 10 000317.022	Black	Phase DIM
	101 10 000315.013	101 10 000316.013	101 10 000317.013	White	DALI
	101 10 000315.213	101 10 000316.023	101 10 000317.023	Black	DALI
	101 10 000315.015	101 10 000316.015	101 10 000317.015	White	Bluetooth
	101 10 000315.215	101 10 000316.025	101 10 000317.025	Black	Bluetooth

**Optical Accessories**

990 00 006501.020	Asymmetrical Lens A1 065
990 00 006502.000	Asymmetrical Lens A2 065
990 00 006503.000	Hex Louvre 065
990 00 006504.000	Spreader Lens 065
990 00 006505.000	Linear Spreader Lens 065
990 00 006506.000	Diffuser Lens 80% Transmission 065
990 00 006507.000	Diffuser Lens 50% Transmission 065
990 00 006508.000	Low UGR Workplace Optic Lens 065

[iilus.com](http://iilus.com)