

Product Manual

Mono 100 Surface Downlighter Type 2




Mono 100 Surface

Type 2



Surface mounted ceiling luminaire with rotationally symmetrical spot, flood or wide flood optics, high colour reproduction, fixed orientation. High pressure die-cast powdercoated facade with expressed detail, anti-glare baffle. Integrated driver. Active power factor correction, current regulation, voltage spike protection. Optional spreader lens, linear spreader lens, diffuser lens, or hex louvre; factory fitted.



System

Power	14W / 19W / 27W
Input	220V-240V / 50-60Hz
Colour Temperature	2700°K / 3000°K / 4000°K
Lumen Maintenance	14W 19W L90 B10 50 000hr / 27W L80 B20 50 000hr
CRI	Ra97
Tm30	R95 F103
Chromacity	<3 SCDM
Articulation	Fixed
Ingress Protection	IP44

14W	SP - 15°	FL - 30°	WFL - 60°
2700°K	956lm	1013lm	981lm
3000°K	953lm	942lm	1037lm
4000°K	1127lm	1095lm	1132lm
19W	SP - 15°	FL - 30°	WFL - 60°
2700°K	1314lm	1300lm	1350lm
3000°K	1320lm	1300lm	1436lm
4000°K	1548lm	1508lm	1568lm
27W	SP - 15°	FL - 30°	WFL - 60°
2700°K	1763lm	1750lm	1765lm
3000°K	1781lm	1770lm	1939lm
4000°K	2091lm	2029lm	2110lm



Model References

14W	FL - 15°	FL - 30°	WFL - 60°		
2700°K	101 10 100200.011	101 10 100201.011	101 10 100202.011	White	Fixed Output
	101 10 100200.211	101 10 100201.021	101 10 100202.021	Black	Fixed Output
	101 10 100200.013	101 10 100201.013	101 10 100202.013	White	DALI
	101 10 100200.213	101 10 100201.023	101 10 100202.023	Black	DALI
	101 10 100200.015	101 10 100201.015	101 10 100202.015	White	Bluetooth
	101 10 100200.215	101 10 100201.025	101 10 100202.025	Black	Bluetooth
3000°K	101 10 100203.011	101 10 100204.011	101 10 100205.011	White	Fixed Output
	101 10 100203.211	101 10 100204.021	101 10 100205.021	Black	Fixed Output
	101 10 100203.013	101 10 100204.013	101 10 100205.013	White	DALI
	101 10 100203.213	101 10 100204.023	101 10 100205.023	Black	DALI
	101 10 100203.015	101 10 100204.015	101 10 100205.015	White	Bluetooth
	101 10 100203.215	101 10 100204.025	101 10 100205.025	Black	Bluetooth
4000°K	101 10 100206.011	101 10 100207.011	101 10 100208.011	White	Fixed Output
	101 10 100206.211	101 10 100207.021	101 10 100208.021	Black	Fixed Output
	101 10 100206.013	101 10 100207.013	101 10 100208.013	White	DALI
	101 10 100206.213	101 10 100207.023	101 10 100208.023	Black	DALI
	101 10 100206.015	101 10 100207.015	101 10 100208.015	White	Bluetooth
	101 10 100206.215	101 10 100207.025	101 10 100208.025	Black	Bluetooth
19W	FL - 15°	FL - 30°	WFL - 60°		
2700°K	101 10 100209.011	101 10 100210.011	101 10 100211.011	White	Fixed Output
	101 10 100209.211	101 10 100210.021	101 10 100211.021	Black	Fixed Output
	101 10 100209.013	101 10 100210.013	101 10 100211.013	White	DALI
	101 10 100209.213	101 10 100210.023	101 10 100211.023	Black	DALI
	101 10 100209.015	101 10 100210.015	101 10 100211.015	White	Bluetooth
	101 10 100209.215	101 10 100210.025	101 10 100211.025	Black	Bluetooth
3000°K	101 10 100212.011	101 10 100213.011	101 10 100214.011	White	Fixed Output
	101 10 10022.211	101 10 100213.021	101 10 100214.021	Black	Fixed Output
	101 10 100212.013	101 10 100213.013	101 10 100214.013	White	DALI
	101 10 100212.213	101 10 100213.023	101 10 100214.023	Black	DALI
	101 10 100212.015	101 10 100213.015	101 10 100214.015	White	Bluetooth
	101 10 100212.215	101 10 100213.025	101 10 100214.025	Black	Bluetooth
4000°K	101 10 100215.011	101 10 100216.011	101 10 100217.011	White	Fixed Output
	101 10 100215.211	101 10 100216.021	101 10 100217.021	Black	Fixed Output
	101 10 100215.013	101 10 100216.013	101 10 100217.013	White	DALI
	101 10 100215.213	101 10 100216.023	101 10 100217.023	Black	DALI
	101 10 100215.015	101 10 100216.015	101 10 100217.015	White	Bluetooth
	101 10 100215.215	101 10 100216.025	101 10 100217.025	Black	Bluetooth

27W	FL - 15°	FL - 30°	WFL - 60°		
2700°K	101 10 100218.011	101 10 100219.011	101 10 100220.011	White	Fixed Output
	101 10 100218.211	101 10 100219.021	101 10 100220.021	Black	Fixed Output
	101 10 100218.013	101 10 100219.013	101 10 100220.013	White	DALI
	101 10 100218.213	101 10 100219.023	101 10 100220.023	Black	DALI
	101 10 100218.015	101 10 100219.015	101 10 100220.015	White	Bluetooth
	101 10 100218.215	101 10 100219.025	101 10 100220.025	Black	Bluetooth
3000°K	101 10 100221.011	101 10 100222.011	101 10 100223.011	White	Fixed Output
	101 10 100221.211	101 10 100222.021	101 10 100223.021	Black	Fixed Output
	101 10 100221.013	101 10 100222.013	101 10 100223.013	White	DALI
	101 10 100221.213	101 10 100222.023	101 10 100223.023	Black	DALI
	101 10 100221.015	101 10 100222.015	101 10 100223.015	White	Bluetooth
	101 10 100221.215	101 10 100222.025	101 10 100223.025	Black	Bluetooth
4000°K	101 10 100224.011	101 10 100225.011	101 10 100226.011	White	Fixed Output
	101 10 100224.211	101 10 100225.021	101 10 100226.021	Black	Fixed Output
	101 10 100224.013	101 10 100225.013	101 10 100226.013	White	DALI
	101 10 100224.213	101 10 100225.023	101 10 100226.023	Black	DALI
	101 10 100224.015	101 10 100225.015	101 10 100226.015	White	Bluetooth
	101 10 100224.215	101 10 100225.025	101 10 100226.025	Black	Bluetooth

Optical Accessories

990 00 006501.020	Asymmetrical Lens A1 065
990 00 006502.000	Asymmetrical Lens A2 065
990 00 006503.000	Hex Louvre 065
990 00 006504.000	Spreader Lens 065
990 00 006505.000	Linear Spreader Lens 065
990 00 006506.000	Diffuser Lens 80% Transmission 065
990 00 006507.000	Diffuser Lens 50% Transmission 065
990 00 006508.000	Low UGR Workplace Optic Lens 065

iilus.com