

Product Manual

Mono 100 Suspension Downlighter Type 2




IILUS

Mono 100 Suspension Type 2



Suspension mounted ceiling luminaire with rotationally symmetrical spot, flood or wide flood optics, high colour reproduction, fixed orientation. High pressure die-cast powdercoated facade with expressed detail, anti-glare baffle. Integrated driver. Active power factor correction, current regulation, voltage spike protection. Optional spreader lens, linear spreader lens, diffuser lens, or hex louvre; factory fitted.



System

Power	14W / 19W / 27W
Input	220V-240V / 50-60Hz
Colour Temperature	2700°K / 3000°K / 4000°K
Lumen Maintenance	14W 19W L90 B10 50 000hr / 27W L80 B20 50 000hr
CRI	Ra97
Tm30	R95 F103
Chromacity	<3 SCDM
Articulation	Fixed
Ingress Protection	IP20

14W	SP - 15°	FL - 30°	WFL - 60°
2700°K	956lm	1013lm	981lm
3000°K	953lm	942lm	1037lm
4000°K	1127lm	1095lm	1132lm
19W	SP - 15°	FL - 30°	WFL - 60°
2700°K	1314lm	1300lm	1350lm
3000°K	1320lm	1300lm	1436lm
4000°K	1548lm	1508lm	1568lm
27W	SP - 15°	FL - 30°	WFL - 60°
2700°K	1763lm	1750lm	1765lm
3000°K	1781lm	1770lm	1939lm
4000°K	2091lm	2029lm	2110lm



Model References

14W	SP - 15°	FL - 30°	WFL - 60°		
2700°K	101 10 200200.011	101 10 200201.011	101 10 200202.011	White	Fixed Output
	101 10 200200.211	101 10 200201.021	101 10 200202.021	Black	Fixed Output
	101 10 200200.013	101 10 200201.013	101 10 200202.013	White	DALI
	101 10 200200.213	101 10 200201.023	101 10 200202.023	Black	DALI
	101 10 200200.015	101 10 200201.015	101 10 200202.015	White	Bluetooth
	101 10 200200.215	101 10 200201.025	101 10 200202.025	Black	Bluetooth
3000°K	101 10 200203.011	101 10 200204.011	101 10 200205.011	White	Fixed Output
	101 10 200203.211	101 10 200204.021	101 10 200205.021	Black	Fixed Output
	101 10 200203.013	101 10 200204.013	101 10 200205.013	White	DALI
	101 10 200203.213	101 10 200204.023	101 10 200205.023	Black	DALI
	101 10 200203.015	101 10 200204.015	101 10 200205.015	White	Bluetooth
	101 10 200203.215	101 10 200204.025	101 10 200205.025	Black	Bluetooth
4000°K	101 10 200206.011	101 10 200207.011	101 10 200208.011	White	Fixed Output
	101 10 200206.211	101 10 200207.021	101 10 200208.021	Black	Fixed Output
	101 10 200206.013	101 10 200207.013	101 10 200208.013	White	DALI
	101 10 200206.213	101 10 200207.023	101 10 200208.023	Black	DALI
	101 10 200206.015	101 10 200207.015	101 10 200208.015	White	Bluetooth
	101 10 200206.215	101 10 200207.025	101 10 200208.025	Black	Bluetooth
19W	FL - 15°	FL - 30°	WFL - 60°		
2700°K	101 10 200209.011	101 10 200210.011	101 10 200211.011	White	Fixed Output
	101 10 200209.211	101 10 200210.021	101 10 200211.021	Black	Fixed Output
	101 10 200209.013	101 10 200210.013	101 10 200211.013	White	DALI
	101 10 200209.213	101 10 200210.023	101 10 200211.023	Black	DALI
	101 10 200209.015	101 10 200210.015	101 10 200211.015	White	Bluetooth
	101 10 200209.215	101 10 200210.025	101 10 200211.025	Black	Bluetooth
3000°K	101 10 200212.011	101 10 200213.011	101 10 200214.011	White	Fixed Output
	101 10 20022.211	101 10 200213.021	101 10 200214.021	Black	Fixed Output
	101 10 200212.013	101 10 200213.013	101 10 200214.013	White	DALI
	101 10 200212.213	101 10 200213.023	101 10 200214.023	Black	DALI
	101 10 200212.015	101 10 200213.015	101 10 200214.015	White	Bluetooth
	101 10 200212.215	101 10 200213.025	101 10 200214.025	Black	Bluetooth
4000°K	101 10 200215.011	101 10 200216.011	101 10 200217.011	White	Fixed Output
	101 10 200215.211	101 10 200216.021	101 10 200217.021	Black	Fixed Output
	101 10 200215.013	101 10 200216.013	101 10 200217.013	White	DALI
	101 10 200215.213	101 10 200216.023	101 10 200217.023	Black	DALI
	101 10 200215.015	101 10 200216.015	101 10 200217.015	White	Bluetooth
	101 10 200215.215	101 10 200216.025	101 10 200217.025	Black	Bluetooth

27W	SP - 15°	FL - 30°	WFL - 60°		
2700°K	101 10 200218.011	101 10 200219.011	101 10 200220.011	White	Fixed Output
	101 10 200218.211	101 10 200219.021	101 10 200220.021	Black	Fixed Output
	101 10 200218.013	101 10 200219.013	101 10 200220.013	White	DALI
	101 10 200218.213	101 10 200219.023	101 10 200220.023	Black	DALI
	101 10 200218.015	101 10 200219.015	101 10 200220.015	White	Bluetooth
	101 10 200218.215	101 10 200219.025	101 10 200220.025	Black	Bluetooth
3000°K	101 10 200221.011	101 10 200222.011	101 10 200223.011	White	Fixed Output
	101 10 200221.211	101 10 200222.021	101 10 200223.021	Black	Fixed Output
	101 10 200221.013	101 10 200222.013	101 10 200223.013	White	DALI
	101 10 200221.213	101 10 200222.023	101 10 200223.023	Black	DALI
	101 10 200221.015	101 10 200222.015	101 10 200223.015	White	Bluetooth
	101 10 200221.215	101 10 200222.025	101 10 200223.025	Black	Bluetooth
4000°K	101 10 200224.011	101 10 200225.011	101 10 200226.011	White	Fixed Output
	101 10 200224.211	101 10 200225.021	101 10 200226.021	Black	Fixed Output
	101 10 200224.013	101 10 200225.013	101 10 200226.013	White	DALI
	101 10 200224.213	101 10 200225.023	101 10 200226.023	Black	DALI
	101 10 200224.015	101 10 200225.015	101 10 200226.015	White	Bluetooth
	101 10 200224.215	101 10 200225.025	101 10 200226.025	Black	Bluetooth

Optical Accessories

990 00 006501.020	Asymmetrical Lens A1 065
990 00 006502.000	Asymmetrical Lens A2 065
990 00 006503.000	Hex Louvre 065
990 00 006504.000	Spreader Lens 065
990 00 006505.000	Linear Spreader Lens 065
990 00 006506.000	Diffuser Lens 80% Transmission 065
990 00 006507.000	Diffuser Lens 50% Transmission 065
990 00 006508.000	Low UGR Workplace Optic Lens 065

Mounting Accessories

980 01 010015.003	Suspension Kit 3 Core Clear Cable 1500mm
980 01 010030.003	Suspension Kit 3 Core Clear Cable 3000mm
980 01 010060.003	Suspension Kit 3 Core Clear Cable 6000mm
980 01 010015.005	Suspension Kit 5 Core Clear Cable 1500mm
980 01 010030.005	Suspension Kit 5 Core Clear Cable 3000mm
980 01 010060.005	Suspension Kit 5 Core Clear Cable 6000mm

iilus.com